



RK600

Auto Refractor/Keratometer

Fast, Accurate, Refractometry and Keratometry.

RK600 Auto Refractor/Keratometer

The Reichert® **RK600** provides quick, easy and accurate objective refractive and keratometric measurements. User-selectable, automatic and manual modes allow the instrument to be customized to your needs and preferences. The operating icons and results are easily viewed on the full color LCD display.

An adjustable chinrest and headrest, familiar joystick control and automatic measurement modes make the RK600 easy for any operator to use.

Refractive and keratometric measurements are highly accurate and provide reliable data for the starting point of a subjective refraction and contact lens fitting.

The instrument's auto start function initiates measurements automatically when alignment is achieved. Between one and ten sequential refractive measurements can be obtained in the automatic mode.

The RK600 enables you to format measurement printouts, which are automatically cut after being dispensed.



Measurement Options

- Refractive Only
- Keratometry Only
- Refractive and Keratometry
- Kerato-Peripheral
- Base Curve of Contact Lens
- Intraocular Lens Measurement
- PD Measurement

Specifications

Catalog Number: 15030 RK600 Auto Refractor/Keratometer

Refractive Measuring Range

Sphere: -25.00D through +25.00D (0.12D, 0.25D steps)

Cylinder: -10.00D through +10.00D (0.12D, 0.25D steps)

Axis: 1° through 180° (1° steps)

Keratometric Measuring Range

Radius of Curvature: 5.00 mm to 10.00 mm (0.01 mm steps)

Corneal Power: 33.75D to 67.50D (0.12D, 0.25D steps)

Cylinder: 0 through ±9D (0.12D, 0.25D steps)

Axis: 0° through 180° (1° steps)

Peripheral: Φ 7.5 mm (when radius of curvature is 8 mm)

Adjustment Range of Instrument

Back/Forth: ±17 mm

Right/Left: ±43 mm

Up/Down: ±17 mm

Other Specifications

Vertical Adjustment

Range for Chin Rest: ±30 mm

Vertex Distance: 0, 10, 12, 13.5, 15 mm

PD Range: 85 mm (1 mm steps)

Min. Pupil Diameter: 2.3 mm

Display: 5.6 inches, color LCD

Printer: Thermal Line Printer with auto-cutter (paper width 57 mm)

Dimensions: 9.4 W x 16.6 D x 17.2 H inches (240 W x 422 D x 437 H mm)

Weight: 33 lbs. (15 kg) - Unpacked

Data Output: RS232C Interface and Video Terminal

Power Source: 100~240 V 50/60 Hz

Consumption: 80 VA

Fuses: 250 VAC, 3 Amps

Power Saving Function: OFF, 3, 5, 10 min. (selectable)

Standard Accessories: Power Cord, Dust Cover, Verification Eye, Printer Paper, Chin Rest, Fuses.



Visit www.reichert.com or contact your Authorized Reichert Technologies Distributor.

Important Notice: For your own protection, purchase instruments from and have them serviced only by Reichert Technologies or an Authorized Reichert Technologies Distributor.

15030-110-Rev-A ©2012 AMETEK, Inc. All rights reserved. - Specifications subject to change without notice. Reichert and Reichert Technologies are registered trademarks of Reichert, Inc. "Advancing Eye Care. Preserving Sight." is a trademark of Reichert, Inc. AMETEK is a registered trademark of AMETEK, Inc.



Reichert, Inc.
3362 Walden Avenue, Depew, NY 14043
Toll Free: 888-849-8955 • Tel: (716) 686-4500
Fax: (716) 686-4545 • www.reichert.com

ISO 9001 Certified
Reichert products are designed and manufactured under quality processes meeting ISO 9001 requirements.